



redPOWER PRISM

Multi kW OEM 3kW - 6kW

Building blocks for high power Fiber Lasers.
CW OEM Fiber Lasers.



Key benefits and features

A true OEM Fiber Laser allowing machine builders to offer a leading edge, highly reliable Fiber Laser based cutting and welding machine maintaining their own brand throughout. This scalable solution uses modules of 1.5kW achieving output powers up to 6kW when combined through the SPI proprietary High Power Combiner (HPC). These Laser modules combine single mode beam quality, high efficiency & reliability, fast modulation capability and easy install features.

Full feature list

- Single modules of 1.5kW output power.
- Combined output power options of 3kW, 4.5kW & 6kW.
- Patented back reflection protection.
- Integrated pierce detection as standard.
- Simple integration into existing equipment.
- Field replaceable delivery fiber.
- Process monitoring capability via back reflected radiation signal.
- Extremely compact design.
- Rack mount 19" format.
- Integrated pulse shaping capability.
- High frequency modulation.


Optimised for...

High volume OEMs' who want:

- To tightly integrate the Fiber Laser within their overall system design.
- To provide 100% of the machine and Laser service to their customers.
- The flexibility to build systems to order, combining individual modules as required.



Cutting
Mild Steel



Welding
Stainless Steel



Cladding
Dissimilar Metals

PRISM concept overview

The Multi-kW PRISM is available with 2, 3 or 4 Fiber Laser modules combined with one High Power Combiner (HPC). This gives total output power options of 3kW, 4.5kW & 6kW. The units can either be ordered as a single pre-configured unit (i.e. Fiber Laser modules spliced into the HPC with a delivery fiber fitted). Or for high volume customers with fiber splicing capabilities, separate modules can be supplied allowing the output power to be customised based on customer orders. This option allows OEMs' to reduce stock and delivery times. The units are 19" rack compatible and can be installed within a separate cabinet or, more interestingly, into the machine itself, so only the OEM's brand name is visible to the end user. The System Integrator adds value to these modules by providing the DC power supply, a suitable enclosure with environmental control where necessary, a temperature controlled coolant supply and system level safety control.

www.spilasers.com | sales@spilasers.com

© SPI Lasers UK Ltd
SM-S00471-4

Benefits

- Lowest cost Laser for high volume manufacturers
- Opportunity for OEMs' to add value. More than a Laser reseller
- We offer OEMs' training for field servicing of modules (including delivery fiber)
- High stability, repeatability & reliability

Key features

- 3kW, 4.5kW & 6kW outputs
- Multiple fiber delivery options
- PIPA-Q fiber termination with industry standard opto-mechanical compatibility and integral patented Back Reflection protection
- Pierce detection signal
- 19" Rack modular design
- Integral pulse shaping capability
- High frequency modulation

Applications

- Thick Sheet Cutting
- Fast Thin Sheet Cutting
- High Speed Welding
- Remote Welding
- Cladding

Industries

- Automotive
- Advanced Manufacturing
- Flat Sheet Cutting
- General Fabrication

Go to spilasers.com for information on our full suite of Pulsed and CW Fiber Lasers.

Product Selection Parameters

Model	3kW	4.5kW	6kW
Performance Data			
Mode Of Operation	CW and Modulated		
Output Power Range	10 -105% of specified power		
Long Term Output Power Stability ⁽¹⁾	± 2% peak		
Wavelength (nm)	1080		
Linewidth (nm)	<10		
Polarisation	Un-polarised		
Min. Rise / Fall Time (µs)	<5 / <6		
Max. Modulation Frequency (kHz)	≤50		
Fiber Optic Beam Delivery			
50µm Fiber	2.1mm.mrad BPP ⁽²⁾	N/A	N/A
100µm Fiber	Enhanced, 3.3mm.mrad BPP ⁽²⁾		
100µm Fiber	4.5mm.mrad BPP ⁽²⁾		
Alignment Laser Wavelength (nm)	630 – 680 (Class 2)		
Electrical			
Voltage (nominal)	48V DC		
Current (A)	240	360	480
Environment / Cooling			
Ambient Temperature (°C)	5-45		
Coolant Flow Rate (litres / min) ⁽³⁾	42	61	76
Coolant Connections	10mm		
Max Relative Humidity	85% (20°C), 50% (40°C)		
Module Dimensions			
Height (mm)	6U (267)	8U (356)	10U (445)
Width (mm)	19" rack mount (445)		
Depth (mm)	702		

Notes

1. Constant Temperature
2. Beam Parameter Product = beam radius x half angle divergence
3. At Maximum 30°C Temperature

Terms and conditions

Some specific combinations of product and optional accessory may not be available. These units are Class 4 Lasers designed as components for incorporation or integration into other equipment. All product information is believed to be accurate and subject to change without notice. A complete product specification will be issued on request and also at time of order acknowledgement. The user assumes all risks and liability whatsoever in connection with the use of the product or its application.


Applications




Cutting
Mild Steel, Copper,
Aluminium, Brass
Stainless Steel



Cutting
Mild Steel



Cutting
Stainless Steel



Cutting
Aluminium

